

TP SPRINKLER CLAMP




■ Product Description

- TP Sprinkler Clamp is recommended to provide vertical support to non-insulated fire extinguishing pipes
- By adjusting the position of the sprinkler nut on the threaded rod at the top of the hanger, pipe elevation can be altered
- Made up of mild steel material
- TP Sprinkler Clamp will handle heavy loads
- TP Sprinkler Clamp comes with sprinkler nut
- Available sizes 3/4" to 10" (other dimensions are available upon request)
- Available finishing material : Electro-Galvanized, Hot Dip Galvanized



■ Approvals

- Underwriter's Laboratories (UL)
- Factory Mutual Approved (FM)
- Electrogalvanized as per ASTM B 633
- Designed to meet MSS Standard SP 58 (type 10) and SP 69



■ Characteristics

Item Number	Nominal Pipe Size		Approval	Pipe Outer Diameter (D) (mm)	Height (L) (mm)	Threaded Rod Size (R)	Maximum Load (KG)
	Inch	mm					
TP 12001	¾"	DN20	UL & FM	26.7	61	M10	300
TP 12002	1"	DN25	UL & FM	33.4	70	M10	300
TP 12003	1 ¼"	DN32	UL & FM	42.1	78	M10	300
TP 12004	1 ½"	DN40	UL & FM	48.2	84	M10	300
TP 12005	2"	DN50	UL & FM	60.3	102	M10	300
TP 12006	2 ½"	DN65		73.0	118	M10	450
TP 12007	3"	DN80	UL & FM	88.9	144	M10	450
TP 12008	4"	DN100	UL & FM	114.3	176	M10	550
TP 12009	5"	DN125	FM	141.3	220	M12	650
TP 12010	6"	DN150	UL & FM	168.3	262	M12	750
TP 12011	8"	DN200	UL & FM	219.1	305	M12	900
TP 12012	10"	DN250		273.0	320	M12	900